#### 6. Function or Use

Historic Function (enter categories from instructions)

TRANSPORTATION/road-related

Current Function (enter categories from instructions)

TRANSPORTATION/road-related

### Description

Architectural Classification (enter categories from instructions)

OTHER /riveted Warren cantilevered through truss

Materials (enter categories from instructions)

foundation N/A N/A walls

N/A roof N/A other

Describe present and historic physical appearance.

Located on the east edge of Brownville, the Brownville Bridge spans the Missouri River on the Nebraska - Missouri state line. Other than maintenance-related repairs, the bridge remains essentially unaltered as it continues to carry vehicular traffic. The Brownville Bridge today retains a high degree of integrity of location, design, setting, materials, workmanship, feeling and association. A description of the structure follows:

span number:

2

construction date: 1939

construction cost: \$708,878.54

span length: total length:

420.0' 1904.0

current condition: good

roadway wdt.:

22.5

alterations:

none

superstructure: steel, rigid-connected Warren cantilever through truss

substructure:

concrete abutments with concrete backwalls and sloped wingwalls; concrete piers

floor/decking:

concrete deck over I-beam stringers

other features: upper chord: 2 channels with cover plate and ventilated bottom plate; lower chord: 2 channels with cover plate and ventilated bottom plate; vertical: wide flange; diagonal: 2 ventilated channels with continuous plate; portal and overhead bracing: I-beam; top lateral: cross-braced I-beam; bottom lateral: cross-braced back-to-back angle-sections.

## 8. Statement of Significance

Certifying official has considered the significance of this property in relation to other properties:

statewide

Applicable National Register Criteria

C N/A Criteria Considerations (Exceptions)

Areas of Significance

Engineering

Period of Significance

1939 (The period of significance is derived from the original construc-

tion date.)

Significant Dates Cultural Affiliation Significant Person 1939 N/A N/A

Architect/Builder (Designer)

(Fabricator)

Ash, Howard, Needles and Tammen, Kansas City MO Bethlehem Steel Company, Pittsburgh PA

(Builder)


Ash, Howard, Needles and Tammen (supervisor); Bethlehem Steel Company (superstructure); C.F. Lytle Company (substructure); C.H.


Atkinson Paving Company (embankments)

State significance of property, and justify criteria, criteria considerations and areas of significance noted above.

The Atchison County (Missouri) Board of Supervisors appears to have initiated the planning for this bridge over the Missouri River, securing the prestigious firm of Ash, Howard, Needles and Tammen (AHNT) for design construction supervision. AHNT modeled the new structure on another two-span, continuous truss bridge they had built over the Missouri River at South Omaha in 1934-35, changing details and construction methods of the previous design to improve aesthetics and reduce cost. Whereas, according to one engineer, a "hodgepodge of deck trusses, girder spans and trestles" were used for the South Omaha approach spans, AHNT used only continuous deck girder approaches for the Brownville Bridge. Construction on the structure began early in 1939, with the Bethlehem Steel Company fabricating and erecting the superstructure, the C.F. Lytle Company building the substructure, and the C.H. Atkinson Paving Company completing the earth embankments. The bridge was completed by October 1939. Total project cost: \$708,878.54. The Missouri Highway Commission provided \$50,000, and the Federal Emergency Administration of Public Works provided a grant of \$311,580. Atchison County issued bonds for the balance of the costs, and operated the bridge as a toll crossing to repay its bondholders and cover maintenance expenses. In 1945 the Nebraska Department of Roads and Irrigation reported that the bridge was in "excellent" condition, although the concrete in the piers was cracking and in need of immediate repair. These repairs were apparently never made. Now a toll-free crossing, the Brownville Bridge is technologically significant for its long-span cantilevered truss design and innovative construction.

For further contextual information regarding bridge building in Nebraska, registration requirements, and property types, see related multiple property listing "Highway Bridges in Nebraska, 1870 - 1942."





The control of the second seco

u.

# United States Department of the Interior National Park Service

93000536

LISTED 19930617

# **National Register of Historic Places Registration Form**

This form is for use in nominating or requesting determinations of eligibility for individual properties or districts. See instructions in *Guidelines for Completing National Register Forms* (National Register Bulletin 16). Complete each item by marking "x" in the appropriate box or by entering the requested information. If an item does not apply to the property being documented, enter "N/A" for "not applicable." For functions, styles, materials, and areas of significance, enter only the categories and subcategories listed in the instructions. For additional space use continuation sheets (Form 10-900a). Type all entries.

1. Name of Property						
historic name other name/site number	Brownville Bridg NEHBS Number					
2. Location						
street & number city, town state NE; MO	east edge of Bro	36 over the Missouri Riv wnville NE; Atchison, MO	ver code		not for pu vicinity zip code	ublication 68321
3. Classification			·	<del> </del>		
Ownership of Property Category of Property	State of Missouri structure			er of Resource buting 0 0 1 0	Noncontributing United by buildings United by	
		in the National Register: 0 way Bridges in Nebraska	a, 1870-1	942		
4. State/Federal Agen	cv Certification					
Register of Historic Places and meets the procedural and professional requirements set forth in 36 CFR P property						y opinion, the
In my opinion, the property X meets does not meet the National Register Criteria.  Signature of commenting or other official Claire F. Blackwell, Deputy SHPO  Missouri Department of Natural Resources  State or Federal agency and bureau					18 Morente 1992 Date	
5. National Park Servi	ce Certification					
I, hereby, certify that this p  entered in the Natio see continual determined eligible to Register see co determined not eligi National Register removed from the National Register other (explain:)	nal Register ion sheet for the National ontinuation sheet					
		Signature of the Keeper			Date of Ac	tion

9. Major Bibliographical References
Nebraska Department of Roads, Structure Inventory and Appraisal: Structure Number S136 24018 Nebraska Department of Roads and Irrigation, Twenty-Third Biennial Report, 1939-1940, p. 23; Nec L. Ashton, "Comments on Design and Construction of Various Mississippi River Bridges," lecture to the American Society of Civil Engineers, Tri-City Section, Davenport, 6 April 1944, copy at the Iowa State Historical Society, Des Moines, Iowa; Henry G. Schlitt, "Missouri River Bridges, Report #2," 7 November 1945, located in Bridge Department Files, Nebraska Department of Roads; field inspection by Jeffrey A. Hess, 19 July 1989.
See continuation shee
Previous documentation on file (NPS):  preliminary determination of individual listing (36 CFR 67) has been requested previously listed in the National Register previously determined eligible by the National Register designated a National Historic Landmark recorded by Historic American Buildings Survey #  Tecorded by Historic American Engineering Record #  Primary location of additional data:  X State historic preservation office Other State agency Federal agency Local government University Other (specify repository:)
10. Geographical Data
Acreage of Property Cadastral Reference USGS Quadrangle UTM References  1.07 acre S18, T5N, R16E; S33, T65N, R42W Peru, NE MO (7.5 Minute Series, 1966) zone 15 easting 274960 northing 4475220  See continuation sheet
Verbal Boundary Description  The nominated property is a narrow, rectangular shaped parcel measuring 1904 feet by 24.5 feet, which is centered on the UTM point listed above. Included within this rectangular parcel are the bridge's superstructure, substructure, floor system, and approach spans.
See continuation sheet
Boundary Justification The nominated structure includes the bridge's superstructure, substructure, floor system, any approach spans and the property on which they rest. These boundaries encompass, but do not exceed, all of the property that has been historically associated with this bridge.

\_\_See continuation sheet

11. Form Prepared By									
name/title organization street & number	Demian Hess, Research Historian Fraserdesign and Hess, Roise and Company 1269 Cleveland Avenue	date telephone	30 June 199 303-669-796						
city or town	Loveland	state	Colorado	zip code	80537				

